
OEM Laser Beam Profiler – 5 MP, CW lasers, bare board

Board-level beam profiling module for integration into lasers, test stations and OEM systems

Spectral range	300 – 1100 nm (sensor response)
Sensor	Monochrome CMOS, rolling shutter – CW lasers only, 1/2.5"
Resolution	2592 × 1944 px (5.0 MP)
Pixel size	2.2 µm
Active area	5.70 × 4.28 mm
ADC	12 bit
Frame rate	49 fps (full frame)
Exposure	16 µs – 658 ms
Trigger / I/O	Trigger in, flash out, 2 GPIO
Interface	USB 3, Type-C, bus powered
Power	0.6 – 1.2 W
Lens mount	None (bare board)
Dimensions	36 × 36 × 8 mm
Mass	≈ 7 g
Operating temperature	0 – 85 °C
Software	IZAK LBP APP: beam width/diameter, centroid, ellipticity and azimuth; peak position/value with saturation indication; fixed ROI or Auto-ROI; automated Pass/Fail test mode with exportable results; image save and measurement export. Optional API/DLL integration and AI Insights & Reporting add-on
Included	OEM module, 3 m USB 3 cable, LBP APP license (USB key)


Typical values; specifications may change without notice. The quotation states the binding configuration.

Outline drawing – dimensions in mm




4× Ø3.2 mounting holes

FRONT VIEW (beam side)



SIDE VIEW

Title OEM Laser Beam Profiler – 5 MP, CW lasers, bare board – outline	**SKU** 35006	**Drawing** IZAK-DWG-35006-01	**Rev** 1.0
Drawn IZAK Scientific, 2026-11-08	**Scale** not to scale	**Mount** No lens mount (bare board)	**3D** 35006_3D.step



3D envelope model (STEP AP214): 35006_3D.step – outline, mounting holes, mount and connector side for mechanical integration. Internal components are not modelled. Keep free space around connectors and components as required.